

## PRODUCT SPECIFICATION

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| <b>Product:</b>            | Latex Disposable Glove                                                       |
| <b>Article No.:</b>        | FSM NR 001                                                                   |
| <b>Style No :</b>          | FSM NR 001 60 PC                                                             |
| <b>Material:</b>           | Natural Rubber                                                               |
| <b>Colour:</b>             | White / Beige, Black                                                         |
| <b>Size:</b>               | XS, S, M, L, XL                                                              |
| <b>Texture / Finishing</b> | Finger textured / Full textured / Polymer coated                             |
| <b>Applications:</b>       | Medical Sector, Cleaning, Light Industrial, Food Handling, Examination Glove |
| <b>Grade:</b>              | AQL 1.5 / AQL 4.0                                                            |



### PHYSICAL DIMENSION:

|                               |            |
|-------------------------------|------------|
| <b>Thickness at palm : mm</b> | 0.10 (min) |
|-------------------------------|------------|

|                            |                   |
|----------------------------|-------------------|
| <b>Width at palm (mm):</b> | XSmall: 80 +/- 5  |
|                            | Small: 85 +/- 5   |
|                            | Medium: 95 +/- 5  |
|                            | Large: 110 +/- 5  |
|                            | XLarge: 118 +/- 5 |

|                     |            |
|---------------------|------------|
| <b>Length (mm):</b> | 240 +/- 10 |
|---------------------|------------|

### Weight / piece (g):

|         |             |
|---------|-------------|
| Xsmall  | 5.0 +/- 0.5 |
| Small:  | 5.5 +/- 0.5 |
| Medium: | 6.0 +/- 0.5 |
| Large:  | 6.5 +/- 0.5 |
| Xlarge: | 7.0 +/- 0.5 |

### TECHNICAL SPECIFICATION

| <b>Tensile Strength</b>   | <b>Unaged</b> | <b>Aged (22hr, 100c)</b> |
|---------------------------|---------------|--------------------------|
| Tensile Strength at break | 18MPa (min)   | 14MPa (min)              |
| Elongation at break       | 650%          | 500%                     |

|                                                 |                                                                                                                                                                                                                       |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>COMPLIANCE &amp; TESTED IN ACCORDANCE TO</b> | ASTM : D 3578 , EN 455 : Part 1,2,3,4 , EU Regulation 2016/ 425, UKCA<br>EN 420 : 2003 + A1: 2009, EN ISO 374-1: 2016, EN 374-2: 2019, EN ISO 374-4: 2019,<br>EN ISO 374-5: 2016, EN 16523-1: 2015, MDR (EU) 2017/745 |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**MANUFACTURED FOR: FILTA SAFETY (MALAYSIA) SDN BHD**

**ADDRESS:** 228, Jalan Perajurit T9,  
Taman Syabas, 31400 Ipoh, Perak,  
Malaysia

**TELEPHONE:** +6055457289 / +60380523351

**FAX** +6055280892 / +60380900999

**EMAIL ADDRESS** [fennlee.lee@filtasafety.com.my](mailto:fennlee.lee@filtasafety.com.my)  
[filtasafety.msia@filta-safety.com](mailto:filtasafety.msia@filta-safety.com)